EXAMINED BY : Yung Chang Hu	EMERGING DISPLAY	FILE NO . CAS-0006510
		ISSUE : OCT.26, 2007
APPROVED BY: David Chang	TECHNOLOGIES CORPORATION	TOTAL PAGE : 28
		VERSION : 1

CUSTOMER ACCEPTANCE SPECIFICATIONS

MODEL NO. :

ET070000DH6

(RoHS)

FOR MESSRS :

_____

CUSTOMER'S APPROVAL

DATE :

_____

BY :

_____

EMERGING DISPLAY TECHNOLOGIES CORPORATION	MODEL NO.	VERSION	PAGE
	ET070000DH6	1	0-1

RECORDS OF REVISION

DOC . FIRST ISSUE

OCT.26, 2007

DATE	REVISED PAGE NO.	SUMMARY

TABLE OF CONTENTS

NO.	ITEM	PAGE
1.	GENERAL SPECIFICATIONS	1
2.	MECHANICAL SPECIFICATIONS	1
3.	ABSOLUTE MAXIMUM RATINGS	2
4.	ELECTRICAL CHARACTERISTICS	3
5.	TIMING CHART	4 , 5
6.	OPTICAL CHARACTERISTICS	6 , 7
7.	OUTLINE DIMENSIONS	8
8.	BLOCK DIAGRAM	9
9.	DETAIL DRAWING OF DOT MATRIX	10
10.	INTERFACE SIGNAL	11 , 12
11.	POWER SUPPLY	13
12.	TOUCH PANEL SPECIFICATION	14 ~ 18
13.	INSPECTION CRITERION	19 ~ 28

1. GENERAL SPECIFICATIONS

1.1 APPLICATION NOTES FOR CONTROLLER/DRIVER

PLEASE REFER TO :

HIMAX HX8232
HIMAX HX8643

1.2 MATERIAL SAFETY DESCRIPTION

ASSEMBLIES SHALL COMPLY WITH EUROPEAN ROHS REQUIREMENTS, INCLUDING PROHIBITED MATERIALS/COMPONENTS CONTAINING LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, POLYBROMINATED BIPHENYLS (PBB) AND POLYBROMINATED DIPHENYL ETHERS (PBDE)

2. MECHANICAL SPECIFICATIONS

(1)	DISPLAY SIZE (inch)	7”
(2)	NUMBER OF DOTS	800W * (RGB) * 480H DOTS
(3)	MODULE SIZE	165W * 104H *9.9D mm (WITHOUT FPC)
(4)	EFFECTIVE AREA	155.6W * 94.6H mm (T/P)
(5)	ACTIVE AREA	152.4W * 91.44H mm (LCD) 154W * 93.04H mm (T/P)
(6)	DOT SIZE	0.0635W * 0.1905H mm
(7)	PIXEL SIZE	0.1905W * 0.1905H mm
(8)	LCD TYPE	TFT , TRANSMISSIVE,ANTE-GLARE
(9)	COLOR	262K (18BIT)
(10)	VIEWING DIRECTION	6 O’CLOCK
(11)	BACK LIGHT	LED , COLOR : WHITE

3. ABSOLUTE MAXIMUM RATINGS

3.1 ELECTRICAL ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	REMARK
POWER VOLTAGE	VCC	-0.5	+5	V	VSS=0
INPUT VOLTAGE	Vin	- 0.3	VCC+0.3	V	

3.2 ENVIRONMENTAL ABSOLUTE MAXIMUM RATINGS.

I T E M	OPERATING		STORAGE		REMARK
	MIN.	MAX.	MIN.	MAX.	
AMBIENT TEMPERATURE	-30°C	80°C	-40°C	80°C	NOTE (1) , (2)
HUMIDITY	NOTE (3)		NOTE (3)		WITHOUT CONDENSATION
VIBRATION	—	2.45 m/s^2 (0.25 G)	—	11.76 m/s^2 (1.2 G)	5~20Hz , 1HR 20~500Hz(20Hz) , 1HR 20~500Hz(500Hz) , 1HR X,Y,Z,TOTAL 3HR
SHOCK	—	29.4 m/s^2 (3 G)	—	490 m/s^2 (50 G)	10 m SECONDS XYZ DIRECTIONS 1 TIME EACH
CORROSIVE GAS	NOT ACCEPTABLE		NOT ACCEPTABLE		

NOTE (1) : Ta AT -40°C : 48HR MAX .
80°C : 168HR MAX .
NOTE (2) : BACKGROUND COLOR CHANGES SLIGHTLY DEPENDING ON AMBIENT TEMPERATURE THIS PHENOMENON IS REVERSIBLE.
NOTE (3) : Ta ≤ 60°C : 90%RH MAX (96HRS MAX).
Ta > 60°C : ABSOLUTE HUMIDITY MUST BE LOWER THAN THE HUMIDITY OF 90%RH AT 60°C(96HRS MAX).

4. ELECTRICAL CHARACTERISTICS

Ta = 25 °C

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	REMARK
POWER SUPPLY	VCC	—	(2.7)	(3.3)	(3.6)	V	
POWER SUPPLY CURRENT FOR LCM	ICC	VCC = (3.3V) LED B/L = ON	—	(510)	(600)	mA	
LOW LEVEL INPUT VOLTAGE	VIL	—	0	—	0.3*VCC	V	
HIGH LEVEL INPUT VOLTAGE	VIH	—	0.7*VCC	—	VCC	V	
OUTPUT LOW VOLTAGE	VOL	IOL = -1mA	VSS	—	VSS+0.4	V	
OUTPUT HIGH VOLTAGE	VOH	IOH = 1mA	VCC-0.4	—	—	V	
FORWARD VOLTAGE	V_F	(I_F=180mA)	—	(10.5)	—	V	NOTE (1)
LED LIFE TIME	—	—	(30000)	(40000)	—	hr	

NOTE (1) : INTERNAL CIRCUIT DIAGRAM OF BACKLIGHT



5 . TIMING CHART



5.1 SYNC MODE SIGNAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	REMARK
CLOCK PERIOD	TCLK	25	34	—	NS	
CLOCK FREQUENCY	FCLK	—	29.5	40	MHZ	
CLOCK LOW LEVEL WIDTH	TWCL	11.2	—	—	NS	
CLOCK HIGH LEVEL WIDTH	TWCH	11.2	—	—	NS	
CLOCK RISE, FALL TIME	TCLKR, TCLKF	—	—	3	NS	
HSYNC PERIOD	THP	890	928	1600	TCLK	
HSYNC PULSE WIDTH	THW	—	48	—	TCLK	
HSYNC BACK PORCH	THBP	—	40	—	TCLK	
HSYNC WIDTH + BACK PORCH	THW+ THBP	88			TCLK	
HORIZONTAL VALID DATA WIDTH	THV	800			TCLK	
HSYNC FRONT PORCH	THFP	THP–THW– THBP–THV			TCLK	
HORIZONTAL BLANK	THBK	THP– THV			TCLK	
VSYNC PERIOD	TVP	514	525	960	THP	
VSYNC PULSE WIDTH	TVW	—	3	—	THP	
VSYNC BACK PORCH	TVBP	29			THP	
VERTICAL DATA VALID WIDTH	TW	480			THP	
VSYNC FRONT PORCH	TVFP	TVP– TVW–TVBP–TW			THP	
VERTICAL BLANK	TVBK	TVP – TW			THP	
DATA SETUP TIME	TDS	5	—	—	NS	
DATA HOLD TIME	TDH	5	—	—	NS	



5.2 DE MODE SIGNAL CHARACTERISTICS

PARAMETER		SYMBOL	MIN.	TYP.	MAX.	UNIT	REMARK
DCLK	PERIOD	TCLK	25	34	—	NS	
	FREQUENCY	FCLK	—	29.5	40	MHZ	
	LOW LEVEL WIDTH	TWCL	11.2	—	—	NS	
	HIGH LEVEL WIDTH	TWCH	11.2	—	—	NS	
	RISE, FALL TIME	TCLKR, CLKF	—	—	3	NS	
	DUTY	—	0.45	0.50	0.55	—	
DE	SETUP TIME	TDES	5	—	—	NS	
	HOLD TIME	TDEH	5	—	—	NS	
	RISE, FALL TIME	TDER, TDEF	—	—	6	NS	
	HORIZONTAL PERIOD	THP	820	928	1600	TCLK	
	HORIZONTAL VALID	THV	800			TCLK	
	HORIZONTAL BLANK	THBK	THP - THV			TCLK	
	VERTICAL PERIOD	TVP	485	525	960	THP	
	VERTICAL VALID	TW	480			THP	
	VERTICAL BLANK	TVBK	TVP - TW			THP	
DATA	SETUP TIME	TDS	5	—	—	NS	
	HOLD TIME	TDH	5	—	—	NS	
	RISE, FALL TIME	TDR, TDF	—	—	6	NS	



6. OPTICAL CHARACTERISTICS (NOTE1)

6.1 OPTICAL CHARACTERISTICS

Ta = 25 ± 2 °C

ITEM		SYMBOL	CONDITION		MIN.	TYP.	MAX.	UNIT	REMARK
VIEWING ANGLE		θ_{y+}	CR ≥ 10	θ_x=0°	—	(60)	—	deg.	(2) (3)
		θ_{y-}			—	(60)	—		
		θ_{x+}		θ_y=0°	—	(70)	—		
		θ_{x-}			—	(70)	—		
CONTRAST RATIO		CR	θx=0° , θy=0°		(300)	(400)	—	—	(3)
RESPONSE TIME		t r (rise)	θx=0° , θy=0°		—	(5)	(10)	msec	(4)
		t f (fall)			—	(15)	(20)		
THE BRIGHTNESS OF MODULE		B	θx=0° , θy=0° (IF = 180mA)		(300)	(400)	—	cd/m2	(5)
COLOR OF CIE COORDINATE	WHITE	x	θx=0° , θy=0° (IF = 180 mA) (NTSC : 45 %)		(0.26)	(0.31)	(0.36)	—	(6)
		y			(0.29)	(0.34)	(0.39)		
	RED	x			(0.56)	(0.61)	(0.66)	—	
		y			(0.30)	(0.35)	(0.40)		
	GREEN	x			(0.26)	(0.31)	(0.36)	—	
		y			(0.49)	(0.54)	(0.59)		
	BLUE	x			(0.09)	(0.14)	(0.19)	—	
		y			(0.11)	(0.16)	(0.21)		
THE UNIFORMITY OF MODULE		—	—		75	80	—	%	—

NOTE (1) : TEST EQUIPMENT SETUP :

AFTER STABILIZING AND LEAVING THE PANEL ALONE AT A GIVEN TEMPERATURE FOR 30 MINUTES , THE MEASUREMENT SHOULD BE EXECUTED. MEASUREMENT SHOULD BE EXECUTED IN A STABLE , WINDLESS , AND DARK ROOM. OPTICAL SPECIFICATIONS ARE MEASURED BY TOPCON BM-7 (FAST) WITH A VIEWING ANGLE OF 2° AT A DISTANCE OF 50cm AND NORMAL DIRECTION.



NOTE (2) : DEFINITION OF VIEWING ANGLE :



NOTE (3) : DEFINITION OF CONTRAST RATIO :

$$\text{CONTRASTRATIO(CR)} = \frac{\text{BRIGHTNESS MEASURED WHEN LCD IS AT "WHITE STATE"}}{\text{BRIGHTNESS MEASURED WHEN LCD IS AT "BLACK STATE"}}$$

NOTE (4) : DEFINITION OF RESPONSE TIME : TR AND TF
THE FIGURE BVELOW IS THE OUTPUT SIGNAL OF THE PHOTO DETECTOR.



NOTE (5) : BRIGHTNESS MEASURED WHEN LCD IS AT ”WHITE STATE”

NOTE (6) : THE 100% TRANSMISSION IS DEFINED AS THE TRANSMISSION OF LCD PANEL WHEN ALL THE INPUT TERMINALS OF MODULE ARE ELECTRICALLY OPENED.

6.2 THE TEST METHOD OF BRIGHTNESS AND UNIFORMITY



UNIT：mm

6.3 THE CALCULATING METHOD OF UNIFORMITY

$$\text{UNIFORMITY}: \left[1 - \frac{\text{MAXIMUN BRIGHTESS} - \text{MINIMUN BRIGHTESS}}{\text{AVERAGE BRIGHTESS}}\right] \times 100\%$$

7. OUTLINE DIMENSIONS



UNIT : mm
SCALE : NTS
NOT SPECIFIED TOLERANCE IS ± 0.5

8. BLOCK DIAGRAM



9. DETAIL DRAWING OF DOT MATRIX



UNIT : mm
SCALE : NTS
NOT SPECIFIED TOLERANCE IS ± 0.1
DOTS MATRIX TOLERANCE IS ± 0.01

10. INTERFACE SIGNALS

10.1 CN2 INTERFACE

PIN NO.	SYMBOL	I/O	FUNCTION
1	U/D	I	U/D=H:OUT1→OUT2→ ------- →OUT480 U/D=L:OUT480→ ------- →OUT2→ OUT1
2	R/L	I	R/L= H:OUT1→OUT2→ ------- →OUT840 R/L=L:OUT840→ ------- →OUT2→ OUT1
3	NC	—	NC
4	VCC	P	POWER SUPPLY (3.3V)
5	VCC	P	POWER SUPPLY (3.3V)
6	VCC	P	POWER SUPPLY (3.3V)
7	VCC	P	POWER SUPPLY (3.3V)
8	NC	—	NC
9	DE	I	DATA ENABLE INPUT
10	VSS	P	GROUND
11	VSS	P	GROUND
12	VSS	P	GROUND
13	B5	I	BLUE DATA BIT5
14	B4	I	BLUE DATA BIT4
15	B3	I	BLUE DATA BIT3
16	VSS	P	GROUND
17	B2	I	BLUE DATA BIT2
18	B1	I	BLUE DATA BIT1
19	B0	I	BLUE DATA BIT0
20	VSS	P	GROUND
21	G5	I	GREEN DATA BIT 5
22	G4	I	GREEN DATA BIT 4
23	G3	I	GREEN DATA BIT 3
24	VSS	P	GROUND
25	G2	I	GREEN DATA BIT 2
26	G1	I	GREEN DATA BIT 1
27	G0	I	GREEN DATA BIT 0
28	VSS	P	GROUND
29	R5	I	RED DATA BIT 5
30	R4	I	RED DATA BIT 4

31	R3	I	RED DATA BIT 3
32	VSS	P	GROUND
33	R2	I	RED DATA BIT 2
34	R1	I	RED DATA BIT 1
35	R0	I	RED DATA BIT 0
36	VSS	P	GROUND
37	MODE	I	DE/SYNC MODE SELECT,NORMALLY PULLED HIGH. H:DE MODE L:SYNC MODE
38	DCLK	I	DOT DATA COLOCK
39	HSYNC	I	HORIZONTAL SYNC INPUT
40	VSYNC	I	VERTICAL SYNC INPUT

10.2 CN1 BACKLIGHT INTERFACE

PIN NO	SYMBOL	FUNCTION
1	VBL+(A)	POWER SUPPLY FOR LED BACKLIGHT (ANODE)
2	VBL-(K)	POWER SUPPLY FOR LED BACKLIGHT (CATHODE)

10.3 CN3 T/P INTERFACE

PIN NO	SYMBOL	FUNCTION
1	YU	TOP PANEL
2	XR	RIGHT PANEL
3	YD	BOTTOM PANEL
4	XL	LEFT PANEL

11. POWER SUPPLY

11.1 POWER SUPPLY FOR LCM



12 . TOUCH PANEL SPECIFICATION

12.1 ELECTRICAL CHARACTERISTICS Ta = 25°C

ITEM	CONDITION	SPEC.	UNIT
LINEARITY	—	< 1.5	%
TRANSMISSION	ASTM D1003	84±3	%
ACTIVATION FORCE	SILICON " FINGER"	10~80	g
TERMINAL RESISTANCE	X AXIS	400 ~ 1200	Ω
	Y AXIS	100 ~ 600	
INSULATION RESISTANCE	DC25V	> 10	MΩ

12.2 ABSOLUTE MAXIMUM RATINGS :

ITEM	MIN.	TYP.	MAX.
OPERATING TEMPERATURE (Top)	-30°C	—	80°C
STORAGE TEMPERATURE (Tst)	-40°C	—	+80°C
INPUT VOLTAGE (V)	—	5	5.5

12.3 PRECAUTIONS IN USE OF TOUCH PANEL

12.3.1 PURPOSE：

IN ORDER TO PREVENT ACCIDENTAL USE AND PERFORMANCE DETERIORATION, PLEASE KEEP THE FOLLOWING PRECAUTIONS AND INHIBITED POINTS.

12.3.2 ITEM AND ILLUSTRATION：

(1) STRUCTURE, AREA DEFINITION

THE STRUCTURE AND THE PERFORMANCE GUARANTEED AREA OF THIS TOUCH PANEL ARE DEFINED BELOW：



THE ABOVE FIGURE IS OUR DESIGN RULE OF TOUCH PANEL.
IF IT CANNOT MEET YOUR REQUIREMENT, PLEASE CONTACT WITH OUR ENGINEERS FOR FURTHER DISCUSSION.

ABOVE FIGURE ILLUSTRATES THE RECOMMENDED BEZEL AND CUSHION DESIGN. IN ORDER TO PREVENT
UNUSUAL PERFORMANCE DEGRADATION AND MALFUNCTION OF A TOUCH PANEL, PLEASE CARRY OUT THE SET
CASE DESIGNING AND A TOUCH PANEL ASSEMBLING METHOD AFTER SURELY CONSIDERING THE DEFINITION OF EACH AREA ILLUSTRATED IN ABOVE FIGURE.

AREA(a)：ACTIVE AREA
THE ACTIVE AREA IS GUARANTEED THE POSITION DATA DETECTABLE PRECISION, OPERATION FORCE AND OTHER OPERATIONS. IT IS STRONGLY RECOMMENDED TO PLACE THE OPERATION BUTTON OR MENU KEYS WITHIN THE ACTIVE AREA. DUE TO STRUCTURE, THE ACTIVE AREA IS LESS DURABLE AT THE EDGE OR CLOSE TO THE EDGE.

AREA(b)：OPERATION NON-GUARANTEED AREA
THIS AREA DOES NOT GUARANTEE A TOUCH PANEL OPERATION AND ITS FUNCTION. WHEN THIS AREA IS PRESSED, TOUCH PANEL SHOWS DEGRADATION OF ITS PERFORMANCE AND DURABILITY SUCH AS A PEN SLIDING DURABILITY BECOMES ABOUT ONE-TENTH COMPARED WITH THE ACTIVE AREA (AREA-(A) AS GUARANTEED AREA) AND ITS OPERATION FORCE REQUIRES ABOUT DOUBLE. ABOUT 0.5 MM OUTSIDE FROM A BOUNDARY OF THE ACTIVE AREA CORRESPONDS TO THIS AREA.

AREA(c)：PRESSING PROHIBITION AREA
THE AREA WHICH FORBIDS PRESSING, BECAUSE AN EXCESSIVE LOAD IS APPLIED TO A TRANSPARENT ELECTRODE (ITO) AND A SERIOUS DAMAGE IS GIVEN TO A TOUCH PANEL FUNCTION BY PRESSING.

AREA(d)：NON-ACTIVE AREA
THE AREA DOES NOT ACTIVATE EVEN IF PRESSED.

(2) CAUTIONS FOR INSTALLING AND ASSEMBLING

(i) DO NOT GIVE EXCESSIVE STRAIN TO THE PRODUCT.

(ii) FLEXIBLE PATTERN CABLE IS CONNECTED TO THE BODY BY THERMAL PRESSURE METHOD. SO, DO NOT APPLY EXCESSIVE FORCES TO THE FLEXIBLE PATTERN. DO NOT ADD AN EXCESSIVE FORCE TO A FPC(FLEX TAIL) THAT MAKES PEELING OFF OF THE FPC FROM THE PRODUCT. DO NOT FIX, ADHERE OR MOUNT ANY ADDITIONAL GOODS ON THE FPC SUCH AS ADDITIONAL FILM/PLATE ON THE FPC, BECAUSE SUCH ADDITIONAL GOODS WILL APPLY A STRESS AT THE FPC BONDING AREA. IT MAY AFFECT THE CONDUCTIVITY OF FPC WITH TOUCH PANEL.

(iii) IN ORDER NOT TO APPLY LOAD ON THE DISPLAY, PROVIDE A CLEARANCE OF AT LEAST 0.3MM BETWEEN THE PRODUCT AND DISPLAY.

(iv) WE RECOMMEND THE DESIGN OF A CASE OR BEZEL SHOULD COVERS THE BOUNDARY OF THE ACTIVE AREA INSIDE IN ORDER TO PREVENT AN OPERATION AT OUTSIDE OF THE ACTIVE AREA WHICH CAN NOT GUARANTEE THE FUNCTION OR DURABILITY (REFER TO ITEM 5.1.2. STRUCTURE, AREA DEFINITION).
BEZEL'S EDGE PART MAY GUIDE THE PEN SLIDING ON THE SAME POSITION REPEATEDLY. IF THE BEZEL IS PLACED OUTSIDE OF THE ACTIVE AREA, IT MAY CAUSE THE DAMAGE OF THE ITO FILM.

(v) PRESSING INSIDE OF BOUNDARY OF THE FRAME(PART (A) AS SHOWN IN BELOW) MAY CAUSES FAULT OPERATION, SO PLEASE DESIGN TO AVOID PRESSING OF TOUCH PANEL AT PART (A) SUCH AS HAVING GASKET/CUSHION AT PART (C). PARTICULARLY THE AREA (B) SHALL BE FREE FROM BURR. THE GASKET/CUSHION MATERIAL AT THE PART (C) SHOULD NOT BE EXCEEDED TO INSIDE OF THE BOUNDARY OF THE FRAME.



(vi) TO PREVENT GIVING DISTORTION TO THE FILM OF THE PRODUCT AND PEELING OFF OF THE FILM FROM THE PRODUCT, DO NOT FIX THE FILM AND A SET CASE OR A SHOCK ABSORBING MATERIAL ADHERED TO A SET CASE BY ADHESION.

(vii) WIPE OFF THE STAIN ON THE PRODUCT BY USING SOFT CLOTH MOISTENED WITH ETHANOL. TAKE CARE NOT TO ALLOW ETHANOL TO SOAK INTO THE JOINT OF UPPER FILM AND BOTTOM GLASS. IT MAY OTHERWISE CAUSE PEELING OR DEFECTIVE OPERATION. DO NOT USE ANY ORGANIC SOLVENT OR DETERGENT OTHER THAN ETHANOL.

(viii) THE CORNERS OF THE PRODUCT ARE NOT CHAMFERED AND ARE SHARP. WHEN POSITIONING AND FIXING THE PRODUCT ON THE CASE, PROVIDE A ROUND PART ON THE CORNER OF THE CASE SO AS NOT TO APPLY LOAD ON THE CORNER OF THE TRANSPARENT TOUCH PANEL.

(ix) DO NOT PRESS THE FILM OF THE PRODUCT WHEN THIS PRODUCT IS BUILT INTO A SET.

(3) CAUTIONS FOR OPERATION

(i) OPERATE IT WITH A POLYACETAL PEN (TIP R0.8 OR OVER) OR A BELLY OF A FINGER WITHOUT APPLYING EXCESSIVE LOAD. NEVER USE ANY MECHANICAL PENCILS, BALL POINT PENS AND HARD FINGERTIPS WHOSE TIP IS HARD FOR INPUT, OTHERWISE MALFUNCTIONS MAY RESULT.

(ii) THE INPUT POSITION MAY BE FLUCTUATED A LITTLE THROUGH LONG-TIME USE. IT IS DESIRABLE TO PROVIDE A ZERO-ADJUSTMENT FUNCTION BY USING A CIRCUIT AND SOFTWARE.

(iii) OPERATION AT THE OUT OF ACTIVE AREA IS OUT OF OUR GUARANTEE. IT CAUSES A SERIOUS DAMAGE OF A TRANSPARENT ELECTRODE. DO NOT OPERATE AT THE OUT OF ACTIVE AREA.

(iv) IN CASE OF CLEANING THE PART OF THE CASE BOUNDARY OF ACCOMPLISHED SET, USE A SOFT CLOTH WITH A FINGER BERRY OR A COTTON BUD. DO NOT CLEAN WITH A THI NG OTHER THAN THE FINGER SUCH AS HARD OR SHARP EDGES LIKE A FINGER NAIL ETC. ON THE CLOTH, BECAUSE IT CAUSE TRANSPARENT CONDUCTIVE FILM CRACKS. PLEASE ADVISE THIS PROHIBITION TO YOUR LAST CUSTOMERS.

12.4 DURABILITY

12.4.1 STYLUS HITTING：

ONE MILLION TIMES OR OVER
NO DAMAGE ON FILM SURFACE
PEN：R8 mm SILICON RUBBER
LOAD：250g
FREQUENCY：240 times/min
MEASUREMENT POSITION:
1 POINT OF TOUCH PANEL ACTIVE AREA
REPEATED：OVER 1,000,000 TIMES

12.4.2 PEN TOUCH SLIDING DURABILITY：

100,000 TIMES OR OVER
WRITING WITH R0.8mm PLASTIC STYLUS PEN; WRITING FORCE 150g
IN ACTIVE AREA.
SPEED IS 60mm/sec.

12.5 STEEL BALL DROP TEST

BY USING F9mm STEEL BALL FROM THE HEIGHT OF 30cm AND FALLING ON TOUCH PANEL SURFACE, MUST PASS BELOW CONDITIONS：

APPEARANCE：THE APPEARANCE WITHOUT ANY CHANGE, INCLUDING THE PANEL BROKEN.



12.6 APPEARANCE INSPECTION

PURPOSE：

TO ESTABLISH APPEARANCE STANDARD AND MAINTAIN PRODUCT QUALITY。

SCOPE：

TOUCH PANEL VIEW AREA WITHIN TOUCH PANEL。

12.6.1 RULE：

INSPECTION CONDITION

(A) ENVIRONMENTAL LUMINANCE：500 LUX。

(B) DISTANCE BETWEEN HUMAN EYES AND PANEL：30 CM

(PANEL MUST BE TESTED UNDER LIGHT TRANSPARENT)。

(C) VISUAL ANGEL： > 60°。

(D) LIGHT SOURCE： FLUORESCENT LIGHT SOURCE。

12.6.2 JUDGE CRITERION：

JUDGEMENT UNDER ABOVE MENTIONED CRITERION (PANEL MUST BE TESTED UNDER LIGHT TRANSPARENT),

TESTING GOODS DEFECT CAN BE VISIBLE WITHIN 10 SECONDS, WHICH WILL BE JUDGED AS MAJOR DEFECTS。

SAMPLING STANDARD：

THE SAMPLING STANDARD WILL BE CONFIRMED BY BOTH OF EDT AND CUSTOMER.

13. INSPECTION CRITERION

13.1 APPLICATION

This inspection standard is to be applied to the LCD module delivered from EMERGING DISPLAY TECHNOLOGIES CORP.(E.D.T) to customers

13.2 INSPECTION CONDITIONS

13.2.1 (1)Observation Distance : 35cm±5cm

(2)View Angle :

Non-operation Condition : ±5°(perpendicular to LCD panel surface)

Operation Condition : ±45° (perpendicular to LCD panel surface)



13.2.2 Environment Conditions :

Ambient Temperature		20°C~25°C
Ambient Humidity		65±20%RH
Ambient Illumination	Cosmetic Inspection	More than 600Lux
	Functional Inspection	300~500 Lux

13.2.3 Inspection lot

Quantity per delivery lot for each model

13.2.4 Inspection method

A sampling inspection shall be made according to the following provisions to judge The acceptability

(a)Applicable standard : MIL-STD-105E

Normal inspection , single sampling

Level Ⅱ

(b)AQL : Major defect : AQL 0.65%

Minor defect : AQL 1.0%

13.3 INSPECTION STANDARDS

13.3.1 VISUAL DEFECTS CLASSIFICATION

TYPE OF DEFECT	INSPECTION ITEM	DEFECT FEATURE	AQL
MAJOR DEFECT	1.DISPLAY ON	• DEFECT TO MISS SPECIFIED DISPLAY FUNCTION, FOR ALL AND SPECIFIED DOTS EX: DISCONNECTION, SHORT CIRCUIT ETC	0.65
	2.BACKLIGHT	• NO LIGHT • FLICKERING AND OTHER ABNORMAL ILLUMINATION	
	3.DIMENSIONS	• SUBJECT TO INDIVIDUAL ACCEPTANCE SPECIFICATIONS	
MINOR DEFECT	1.DISPLAY ZONE	• BLACK/WHITE SPOT • BUBBLES ON POLARIZER • NEWTON RING • BLACK/WHITE LINE • SCRATCH • CONTAMINATION • LEVER COLOR SPREED	1.0
	2.BEZEL ZONE	• STAINS • SCRATCHES • FOREIGN MATTER	
	3.SOLDERING	• INSUFFICIENT SOLDER • SOLDERED IN INCORRECT POSITION • CONVEX SOLDERING SPOT • SOLDER BALLS • SOLDER SCRAPS	
	4.DISPLAY ON (ALL ON)	• LIGHT LINE	

13.3.2 MODULE DEFECTS CALSSIFICATION

<table>
<tr><th>NO.</th><th>ITEM</th><th>CRITERIA</th></tr>
<tr><td>1.</td><td>DISPLAY ON INSPECTION</td><td>(1)INCORRECT PATTERN
(2)MISSING SEGMENT
(3)DIM SEGMENT
(4)OPERATING VOLTAGE BEYOND SPEC</td></tr>
<tr><td>2.</td><td>OVERALL DIMENSIONS</td><td>(1)OVERALL DIMENSION BEYOND SPEC</td></tr>
<tr><td>3.</td><td>BLACK SPOTS, FOREIGN MATTER, AND WHITE SPOTS (INCLUDING LIGHT LEAKAGE DUE TO POLARIZING PLATES PINHOLES, ETC.)</td><td>(1) SPOTS
<table>
<tr><th>AVERAGE DIAMETER (mm): D</th><th>NUMBER OF PIECES PERMITTED</th><th>MINIMUM SPACE</th></tr>
<tr><td>D≤0.2</td><td>IGNORE</td><td>—</td></tr>
<tr><td>0.2<D≤0.4</td><td>5</td><td>10 mm</td></tr>
<tr><td>0.4<D</td><td>0</td><td></td></tr>
</table>
NUMBER OF TOTAL PIECES IS TO BE SET WITHIN 5 PIECES.
NOTE :
THAT WHEN THERE ARE 2 PIECES OR MORE, THEY ARE NOT TO BE CONSIDERED AS CONCENTRATED.
(2) BLURRY SPOTS (WHEN FULLY POWERED-ON)
<table>
<tr><th>AVERAGE DIAMETER (mm): D</th><th>NUMBER OF PIECES PERMITTED</th></tr>
<tr><td>D≤0.3</td><td>IGNORE</td></tr>
<tr><td>0.3<D≤0.75</td><td>5</td></tr>
<tr><td>0.75<D</td><td>0</td></tr>
</table>
Note ：Diameter D=(a+b)/2
 

NUMBER OF TOTAL PIECES IS TO BE SET WITHIN 5 PIECES.
NOTE :
THAT WHEN THERE ARE 2 PIECES OR MORE, THEY ARE NOT TO BE CONSIDERED AS CONCENTRATED.</td></tr>
<tr><td>4.</td><td>BLACK LINE
WHITE LINE
NON-DISPLAY</td><td>(1)THE BLACK LINE, WHITE LINE ARE WITHIN THE VIEWING AREA. IT IS NOT ALLOW.</td></tr>
<tr><td>5</td><td>BLACK LINE WHITE LINE ON-DISPLAY</td><td>(1) THE FOLLOWING BLACK LINE , WHITE LINE ARE WITHIN THE VIEWING AREA. WIDTH :Wmm , LENGH :Lmm
<table>
<tr><th>LENGTH : L</th><th>WIDTH : W</th><th>PERMISSIBLE NO.</th></tr>
<tr><td>L ≤ 0.5</td><td>W ≤ 0.1</td><td>IGNORE</td></tr>
<tr><td>0.5 < L ≤ 2.5</td><td>0.1 < W ≤ 0.3</td><td>4</td></tr>
<tr><td>2.5 < L</td><td>0.3 ≤ W</td><td>NONE</td></tr>
</table></td></tr>
<tr><td>6.</td><td>SCRATCHES AND DENT ON GLASS POLARIZER</td><td>(1) PLS REFER TO THE ABOVE NO.3 AND 4 TO DETERMINE SCRATCHES AND DENT ON POLARIZER OR GLASS</td></tr>
<tr><td>7.</td><td>DOT DEFECT ON DISPLAY</td><td>Judgment Criteria
<table>
<tr><th>Area</th><th>Bright Dot</th><th>Dark Dot</th><th>Total</th></tr>
<tr><td>A</td><td>3</td><td>3</td><td>4</td></tr>
<tr><td>B</td><td>5</td><td>5</td><td>5</td></tr>
</table>
(1)It is defined as Point Defect if defect area>0.5dot
(2)It is ignored if defect area≤0.5dot
(3)Weak point defect will be defined as Bright Dot if it can be observed through ND filter 6%
(4)The distance between 2 dot defect≥5mm
(5)Not Allowed Joint point defect
Note : A/B Area Definition
 
</td></tr>
</table>

<table>
<tr><th>NO.</th><th>ITEM</th><th>CRITERIA</th></tr>
<tr><td>8</td><td>LINE DEFECT ON DISPLAY</td><td>OBVIOUS VERTICAL OR HORIZONTAL LINE DEFECT IS NOT ALLOW</td></tr>
<tr><td>9</td><td>MURA ON DISPLAY</td><td>IT’S OK IF MURA IS SLIGHT VISIBLE THROUNG 6% ND FILTER</td></tr>
<tr><td>10</td><td>CF FAIL/SPOT ON DISPLAY</td><td>(1)THE FOLLOWING CF FAIL , SPOT ARE WITHIN THE VIEWING AREA
<table>
<tr><th>SIZE D</th><th>PERMISSIBLE NO.</th></tr>
<tr><td>D ≤ 0.15mm</td><td>IGNORED</td></tr>
<tr><td>0.15mm<D≤0.2mm</td><td>N ≤ 2</td></tr>
<tr><td>D > 0.2mm</td><td>NOT ALLOWED</td></tr>
</table>
Note ：Diameter D=(a+b)/2
 
</td></tr>
<tr><td>11</td><td>UNEVEN COLOR SPREAD , COLORATION</td><td>(1)TO BE DETERMINED BASED UPON THE STANDARD SAMPLE.</td></tr>
<tr><td>12</td><td>BEZEL APPEARANCE</td><td>(1)BEZEL MAY NOT HAVE RUST, E DEFORMED OR HAVE FINGER PRINTS STAINS OF OTHER CONTAMINATION.
(2)BEZEL MUST COMPLY WITH JOB SPECIFICATIONS.</td></tr>
<tr><td>13</td><td>SOLDERING</td><td>(1)NO SOLDERING FOUND ON THE SPECIFIED PLACE
(2)INSUFFICENT SOLDER

(a)LSI, IC
A POOR WETTING OF SOLDER IS BETWEEN LOWER BEND OR “HEEL” OF LEAD AND PAD
 

(b)CHIP COMPONENT
. SOLDER IS LESS THAN 50% OF SIDES AND FRONT FACE WETTING
 
</td></tr>
</table>

NO.	ITEM	CRITERIA
13.	SOLDERING	• SOLDER WETS 3 SIDES OF TERMINAL, BUT LESS THAN 25% OF SIDES AND FRONT SURFACE AREA ARE COVERED  (3)PARTS ALIGMENT (a)LSI, IC LEAD WIDTH IS MORE THAN 50% BEYOND PAD OUTLINE  (b)CHIP COMPONENT COMPONENT IS OFF CENTER, AND MORE THAN 50% OF THE LEADS IS OFF THE PAD OUTLINE 

NO.	ITEM	CRITERIA
13.	SOLDERING	(4)NO UNMELTED SOLDER PASTE MAY BE PRESENT ON THE PCB. (5)NO COLD SOLDER JOINTS, MISSING SOLDER CONNECTIONS, OXIDATION OR ICICLE. (6)NO RESIDUE OR SOLDER BALLS ON PCB. (7)NO SHORT CIRCUITS IN COMPONENTS ON PCB.
14.	BACKLIGHT	(1)NO LIGHT (2)FLICKERING AND OTHER ABNORMAL ILLUMINATION (3)SPOTS OR SCRATCHES THAT APPEAR WHEN LIT MUST BE JUDGED USING LCD SPOT, LINES AND CONTAMINATION STANDARDS. (4)BACKLIGHT DOESN'T LIGHT OR COLOR IS WRONG.
15.	GENERAL APPEARANCE	(1)NO OXIDATION,CONTAMINATION, URVES OR,BENDS ON INTERFACE PIN (OLB) OF TCP. (2)NO CRACKS ON INTERFACE PIN (OLB) OF TCP. (3)NO CONTAMINATION, SOLDER RESIDUE OR SOLDER BALLS ON PRODUCT. (4)THE IC ON THE TCP MAY NOT BE DAMAGED, CIRCUITS. (5)THE UPPERMOST EDGE OF THE PROTECTIVE STRIP ON THE INTERFACE PIN MUST BE PRESENT OR LOOK AS IF IT CAUSE THE INTERFACE PIN TO SEVER. (6)THE RESIDUAL ROSIN OR TIN OIL OF SOLDERING (COMPONENT OR CHIP COMPONENT) IS NOT BURNED INTO BROWN OR BLACK COLOR. (7)SEALANT ON TOP OF THE ITO CIRCUIT HAS NOT HARDENED. (8)PIN TYPE MUST MATCH TYPE IN SPECIFICATION SHEET. (9)LCD PIN LOOSE OR MISSING PINS. (10)PRODUCT PACKAGING MUST THE SAME AS SPECIFIED ON PACKAGING SPECIFICATION SHEET. (11)PRODUCT DIMENSION AND STRUCTURE MUST CONFORM TO PRODUCT SPECIFICATION SHEET. (12)THE APPEARANCE OF HEAT SEAL SHOULD NOT ADMIT ANY DIRT AND BREAK.

<table>
<tr><th>NO.</th><th>ITEM</th><th>CRITERIA</th></tr>
<tr><td rowspan="5">16.</td><td rowspan="5">CRACKED GLASS</td><td>THE LCD WITH EXTENSIVE CRACK IS NOT ACCEPTABLE</td></tr>
<tr><td>General glass chip :
 

<table>
<tr><th>a</th><th>b</th><th>c</th></tr>
<tr><td>≤ t/2</td><td>< VIEWING AREA</td><td>≤ 1/8X</td></tr>
<tr><td>t/2 > , ≤ 2t</td><td>≤ W/2</td><td>≤ 1/8X</td></tr>
</table>
*W=DISTANCE BETWEEN SEALANT AREA AND LCD PANEL EDGE.
X = LCD SIDE LENGTH
t = GLASS THICKNESS</td></tr>
<tr><td>Corner part:
 

<table>
<tr><th>a</th><th>b</th><th>c</th></tr>
<tr><td>≤ t/2</td><td>< VIEWING AREA</td><td>≤ 1/8X</td></tr>
<tr><td>> t/2 , ≤ 2t</td><td>≤ W/2</td><td>≤ 1/8X</td></tr>
</table>
*W=DISTANCE BETWEEN SEALANT AREA AND LCD PANEL EDGE.
X=LCD SIDE LENGTH
t =GLASS THICKNESS</td></tr>
<tr><td>CHIP ON ELECTRODE PAD
 

<table>
<tr><th>a</th><th>b</th><th>c</th></tr>
<tr><td>≤ t</td><td>≤ 0.5mm</td><td>≤ 1/8X</td></tr>
</table>
* X=LCD SIDE WIDTH
t =GLASS THICKNESS</td></tr>
<tr><td> 

<table>
<tr><th>a</th><th>b</th><th>c</th></tr>
<tr><td>≤ t</td><td>≤ 1/8X</td><td>≤ L</td></tr>
</table>
*X=LCD SIDE WIDTH
t = GLASS THICKNESS
L=ELECTRODE PAD LENGTH
①IF GLASS CHIPPING THE ITO TERMINAL, OVER 2/3 OF THE ITO MUST REMAIN AND BE , INSPECTED ACCORDING TO ELECTRODE TERMINAL SPECIFICATIONS
②IF THE PRODUCT WILL BE HEAT SEALED BY THE CUSTOMER, THE ALIGNMENT MARK MUST NOT BE DEMAGED</td></tr>
</table>

13.4 RELIABILITY TEST

13.4.1 STANDARD SPECIFICATIONS FOR RELIABILITY OF LCD MODULE

NO	ITEM	DESCRIPTION
1	High temperature operation	The sample should be allowed to stand at +80°C for 240 hrs
2	Low temperature operation	The sample should be allowed to stand at -30°C for 240 hrs
3	High temperature storage	The sample should be allowed to stand at +80°c for 240 hrs
4	Low temperature storage	The sample should be allowed to stand at -40°C for 240 hrs
5	High temp / humidity test	The sample should be allowed to stand at 60°C , 90% RH 240 hrs
6	Thermal shock (not operated)	The sample should be allowed to stand the following 200 cycles of operation: -25°c for 30 minutes ~ +70°c for 30 minutes
7	ESD (Electrostatic Discharge)	AIR DISCHARGE ± 4KV CONTACT DISCHARGE ± 2KV

NOTE (1) : THE TEST SAMPLES HAVE RECOVERY TIME FOR 2 HOURS AT ROOM TEMPERATURE BEFORE THE FUNCTION CHECK. IN THE STANDARD CONDITIONS , THERE IS NO DISPLAY FUNCTION NG ISSUE OCCURRED.

13.5 TESTING CONDITIONS AND INSPECTION CRITERIA

For the final test the testing sample must be stored at room temperature for 24 hours, after the tests listed in table 12.5 , standard specifications for reliability have been executed in order to ensure stability .

NO	ITEM	TEST MODEL	INSPECTION CRITERIA
1	Current consumption	Refer To Specification	The current consumption should conform to the product specification.
2	Contrast	Refer TO Specification	After the tests have been executed, the contrast must be larger than half of its initial value prior to the tests.
3	Appearance	Visual inspection	Defect free

13.6 OPERATION

13.6.1 Do not connect or disconnect modules to or from the main system while power is being supplied .

13.6.2 Use the module within specified temperature ; lower temperature causes the retardation of blinking speed of the display ; higher temperature makes overall display discolor . When the temperature returns to normality , the display will operate normally .

13.6.3 Adjust the LC driving voltage to obtain the optimum contrast .

13.6.4 Power On Sequence input signals should not be supplied to LCD module before power supply voltage is applied and reaches the specified value . If above sequence is not followed , CMOS LSIs of LCD modules may be damaged due to latch - up problem .

13.7 NOTICE

13.7.1 Use a grounded soldering iron when soldering connector I/O terminals . For soldering or repairing , take precaution against the temperature of the soldering iron and the soldering time to prevent peeling off the through-hole-pad .

13.7.2 Do not disassemble . EDT shall not be held responsible if the module is disassembled and upon the reassembly the module failed .

13.7.3 Do not charge static electricity , as the circuit of this module contains CMOS LSIs. A workman's body should always be static-protected by use of an ESD STRAP . Working clothes for such personnel should be of static-protected material .

13.7.4 Always ground the electrically-powered driver before using it to install the LCD module. While cleaning the work station by vacuum cleaner, do not bring the sucking mouth near the module ; static electricity of the electrically-powered driver or the vacuum cleaner may destroy the module .

13.7.5 Don’t give external shock.

13.7.6 Don’t apply excessive force on the surface.

13.7.7 Liquid in LCD is hazardous substance. Must not lick and swallow. When the liquid is attach to your, skin, cloth etc. Wash it out thoroughly and immediately.

13.7.8 Don’t operate it above the absolute maximum rating.

13.7.9 Storage in a clean environment, free from dust, active gas, and solvent.

13.7.10 Store without any physical load.

13.7.11 Rewiring: no more than 3 times .